

TG3 Series Tag & Label Printers

Performance, Convenience & Versatility



Print, Cut and Stack Operation
(Stacker Optional)



Large Media Supply



Large, Easy to Read LCD Display



Optional Programmable Keypad
(Stand-Alone Operation)



Streamlined Features

- High Throughput, up to 10ips Print Speed
- Thick Tags Supported
- Print, Cut and Stack Media
- Batch Separation Function
- Coreless Ribbon Supported
- Multiple Communication Interfaces USB/LAN/WLAN

Industry Verticals

- Retail Point of Sale
- Home Improvement
- Travel & Leisure
- Postal Services
- Security
- Hospitality
- Outlet Sales

Industry Applications

- Shelf Labels
- Bag and Sack Tagging
- Jewelry Tagging
- Asset Tagging
- Apparel Tagging
- Security Tagging
- Durable Goods
- Price Ticketing
- Mark Down Ticketing

MODEL		TG308	TG312
PRINTING SPECIFICATION			
Print Method		Direct Thermal/Thermal Transfer	
Print Resolution		203dpi (8 dots/mm)	305dpi (12 dots/mm)
Print Speed		Max. 10 ips (250mm/sec)	
Max. Print Area		3.1" (80 mm) x 9.4" (240 mm)	
Memory		8 MB Flash ROM, 16 MB SDRAM	
MEDIA SPECIFICATION			
Sensor Type		I-Mark Sensor (Reflection type), Label Gap Sensor (Transmissive type)	
Media Type		Roll and Fanfold (Face-in, Face-out)	
Media Size	Label (Continuous)	Width: 0.9" to 3.1" (22 to 80 mm) Pitch: 0.6" to 9.3" (16 to 237 mm)	
	Label (Cutter)	Width: 0.9" to 3.1" (22 to 80 mm) Pitch: 0.9" to 9.3" (22 to 237 mm)	
	Tag (Continuous)	Width: 1.3" to 3.3" (32 to 83 mm) Pitch: 1.0" to 9.4" (25 to 240 mm)	
	Tag (Cutter)	Width: 1.3" to 3.3" (32 to 83 mm) Pitch: 1.0" to 9.4" (25 to 240 mm)	
	Thickness	Label: 0.006" to 0.01" (0.14 to 0.265 mm) Tag: 0.006" to 0.013" (0.157 to 0.33 mm)	
	Roll Specs	Max O.D.: 10" (250 mm) - I.D.: 3" (76.4 mm) and 4" (102 mm)	
Ribbon (TT only)		Width: Max. 3.3" (84 mm), Max outer diameter: 1476' (450 m), Face-out/ Face-In	
FONT / SYMBOLOGIES			
Internal Fonts		XU, XS, XM, XB, XL, OCR-A (15x22, 22x33), OCR-B (20x24, 30x36), CG Times, CG Triumvirate	
Barcode Symbologies	Linear	UPC-A/UPC-E, JAN/EAN, CODE39, CODE93, CODE128, GS1-128(UCC/EAN128), CODABAR(NW-7), ITF, Industrial 2of5, Matrix 2of5, BOOKLAND, MSI, POSTNET, GS1 DataBar(RSS) barcode	
	2-D	QR code, MicroQR, PDF417, MicroPDF, MAXI code, GS1 DataMatrix (ECC200)	
	Composite Symbols	EAN-13 Composite, EAN-8 Composite, UPC-A Composite, UPC-E Composite, GS1 DataBar Composite, GS1 DataBar Truncated Composite, GS1 DataBar Stacked Composite, GS1 DataBar Stacked Omni-Directional Composite, GS1 DataBar Limited Composite, GS1 DataBar Expanded Composite, GS1 DataBar Expanded Stacked Composite, GS1-128 Composite	
INTERFACE CHARACTERISTICS			
Interfaces		Plug-In Interface Card, RS232C for Keypad, EXT Port Interface Plug-In Interface Card Options: IEEE1284, RS232C, USB, LAN, Wireless LAN	
Command		SBPL (Ver 4.2) SATO Barcode Printer Language	
OPERATING CHARACTERISTICS			
Power Requirements		Input power voltage: AC 100V - 240V, +/-10% (Full range), 132W / 134VA (Print ratio 30%) In standby: 20W / 22VA	
Environment	Operating	41 to 104 F (5° to 40°C), 30 to 80% RH, Non-condensing	
	Storage	23 to 140 F (-5° to 60°C), 30 to 90% RH, Non-condensing	
Regulatory Approvals		FCC ISB Class B, VL60950-1(2001), CSA222, FCC ISC	
Dimensions		11.18" (284 mm) W x 21.73" (552 mm) D x 11.81" (300 mm) H	
Weight		35.71 lbs. (16.2 kg)	
OTHER			
Optional Accessories		Stacker, Rewinder, SATO Keypad, SOLO Keyboard, SATO Label Gallery™	

SATO America, Inc.

10350-A Nations Ford Road, Charlotte, NC 28273
 Phone: (704) 644-1650 Fax: (704) 644-1662
 E-mail: satosales@satoamerica.com

©2011 SATO America, Inc. All rights Reserved. Rev C • Specifications subject to change without notice • Any unauthorized reproduction of the contents of this content, in part or whole, is strictly prohibited • SATO is a registered trademark of SATO Corporation and its subsidiaries in Japan, the U.S. and other countries. All other trademarks are the property of their respective owners.

Legacy Technology Services

We Rent & Sell All Types Of Barcode Equipment

Call now to talk to an expert

866-271-9891

www.LegacyGlobal.com

Some brands we carry



MOTOROLA

Intermec

DATALOGICTM

Honeywell

EQUINOX
PAYMENTS



About us

- Legacy Technology Services is a leading nationwide provider of mobile computing, barcode, printers and point of sale equipment and services.
- For over a decade, thousands of clients across North America have trusted us to provide equipment from leading manufacturers backed by the services to support them.

Latest Hardware from top manufacturers

- Legacy handles virtually every major manufacturer of mobile computing, barcoding and point of sale equipment.

Expert Repair and Maintenance services

- Legacy is one of the best repair facilities in North America

Discontinued product sourcing

- They don't make it anymore? Our inventory also includes manufacturer close-outs and discontinued equipment to support our clients legacy infrastructure.

Trade-in and Disposal services

- That old equipment laying around your facility may still have some value. Legacy routinely purchases equipment from our clients around the globe.
 - Data destruction
 - Hardware disposal
 - Auditing services

Dedicated client account team

- Dedicated, highly trained account managers are here to answer all your questions and provide top notch service.

Equipment rental services

- Sometimes renting is a better solution, Legacy's huge rental inventory provides the equipment you need for temporary needs and projects.



Legacy, Inc.

160 West Road,
Ellington, CT 06029

Toll Free: 866-271-9891

Fax: 888-522-4684